



Wall mounted unit

FTXA-BT + RXA-A / RXA-B

stylish



Coanda effect - cooling



Coanda effect - heating



Intelligent thermal sensor



Online controller



Multi model application

Where innovation meets creativity

- › Compact design in blackwood
- › Perfect temperature distribution thanks to Coanda effect
- › Intelligent thermal sensor: air flow is adjusted when detecting temperature differences
- › Online controller via app
- › Daikin Flash Streamer technology: powerful air purification
- › Practically inaudible
- › Bluevolution range: lower environmental impact
- › Seasonal efficiency values up to A+++ in cooling and heating

FTXA-BT + RXA-A / RXA-B



RXA-B

FTXA-BT

Efficiency data		FTXA + RXA	20BT + 20A	25BT + 25A	35BT + 35A	42BT + 42B	50BT + 50B
Cooling capacity	Min./Nom./Max.	kW	1.3 /2.0 /2.6	1.3 /2.5 /3.2	1.4 /3.4 /4.0	1.70 /4.20 /5.00	1.70 /5.00 /5.30
Heating capacity	Min./Nom./Max.	kW	1.30 /2.50 /3.50	1.30 /2.80 /4.70	1.40 /4.00 /5.20	1.70 /5.40 /6.00	1.70 /5.80 /6.50
Power input	Cooling	Min./Nom./Max.	kW	0.27 /0.43 /0.63	0.27 /0.56 /0.78	0.31 /0.78 /1.04	-/1.05 /-
	Heating	Min./Nom./Max.	kW	0.25 /0.50 /0.91	0.25 /0.56 /1.22	0.26 /0.99 /1.67	-/1.31 /-
Space cooling	Energy efficiency class		A+++			A++	
	Capacity	Pdesign	kW	2.00	2.50	3.40	5.00
	SEER			8.75	8.74	8.73	7.33
	Annual energy consumption		kWh/a	80	101	137	239
Space heating (Average climate)	Energy efficiency class		A+++			A++	
	Capacity	Pdesign	kW	2.40	2.45	2.50	4.00
	SCOP/A				5.15		4.60
	Annual energy consumption		kWh/a	653	666	680	1,217
Nominal efficiency	EER			4.70	4.46	4.37	3.68
	COP			5.00		4.04	4.00
	Annual energy consumption		kWh		-		526
	Energy labeling Directive	Cooling/Heating		A/A			679

Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. | Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. | See separate drawing for operation range | See separate drawing for electrical data

Indoor unit		FTXA		20BT	25BT	35BT	42BT	50BT	
Dimensions	Unit	HeightxWidthxDepth		mm					
				295 x798 x189					
Weight	Unit			kg					
				11.5					
Air filter	Type	Removable / washable							
Fan	Air flow rate	Cooling	Silent operation/Low/Medium/High	m³/min	4.6 /6.1 /8.2 /11.0	4.6 /6.1 /8.6 /11.5	4.6 /6.1 /8.6 /11.9	4.6 /7.2 /9.8 /13.1	5.2 /7.6 /10.4 /13.5
		Heating	Silent operation/Low/Medium/High	m³/min	4.5 /6.4 /8.7 /10.9	4.5 /6.4 /9.0 /11.1	4.5 /6.4 /9.0 /11.5	5.2 /7.7 /10.5 /14.6	5.7 /8.2 /11.1 /15.1
Sound power level	Cooling			dBA			57		
Sound pressure level	Cooling	Silent operation/Low/High	dBA		19 /25 /39		19 /25 /40		
	Heating	Silent operation/Low/High	dBA		19 /25 /39		19 /25 /40		
Control systems	Infrared remote control		ARC466A58						
	Wired remote control		BRC073						

Outdoor unit		RXA/RXA		20A	25A	35A	42B	50B
Dimensions	Unit	HeightxWidthxDepth		mm				
				550 x765 x285				
Weight	Unit			kg				
				32				
Sound power level	Cooling			dBA			59	
	Heating			dBA			61	
Sound pressure level	Cooling	Nom.	dBA		46		49	
	Heating	Nom.	dBA		47		49	
Operation range	Cooling	Ambient	Min.~Max.	°CDB		-10 ~46		
	Heating	Ambient	Min.~Max.	°CWB		-15 ~18		
Refrigerant	Type	R-32						
	GWP	675.0						
Piping connections	Charge	kg/TCO2Eq		0.76 /0.52			1.10 /0.75	
	Liquid	OD	mm		635			
	Gas	OD	mm		9.50			
	Piping length	OU - IU	Max.	m		20		
	Additional refrigerant charge	kg/m		0.02 (for piping length exceeding 10m)				
	Level difference	IU - OU	Max.	m		15.0		
Power supply	Phase/Frequency/Voltage	Hz/V		1~/50 /220-240				
Current - 50Hz	Maximum fuse amps (MFA)	A		-				

Contains fluorinated greenhouse gases | See separate drawing for operation range | See separate drawing for electrical data

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: www.eurovent-certification.com

ECPEN20-052 02/2020



The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.